

WaterTechw² C4E

Combined Conductivity, Salinity and Temperature Sensor

PRODUCT DATASHEET

APPLICATIONS

Final Effluent Monitoring
Intake Protection
Inlet Monitoring
Potable Water Treatment
River Monitoring

MEASUREMENT PRINCIPAL

4 Electrode Probe

PARAMETERS

Conductivity
Salinity
Temperature

FEATURES

4 Electrodes (2 Graphite, 2 Platinum)
Calibration Data stored in sensor

BENEFITS

Automated Aeration Control
Low Cost Of Ownership

COMPATIBLE MONITOR

7300w² Monitor

ALTERNATIVE SENSORS

Sensors for specialist application are
available on request



The WaterTechw² C4E Sensor has been designed to provide highly reliable Conductivity, Salinity and Temperature measurements. The multi-range sensor allows the same sensor to be employed in a wide variety of applications, the monitoring system being set up to provide the optimum accuracy and resolution for the intended application.

Conductivity is broad measurement that indicates the level of dissolved minerals in the water, for process waters it is an indicator that the water purifier system is not working. In some cases it can be used to prevent problems with scaling due to hardness of tap water, especially in boiler feed water. In many applications Conductivity can be used as a measurement of Total Dissolved Solids (TDS) and is a useful general indicator of water quality.


For installation in applications where fouling is anticipated we recommend that the sensor is installed using our specially designed mounting system, with flexible joint in the mounting shaft. The flexible joint moves the sensor in the process, reducing bio-fouling and allowing rags to fall away from assembly. This motion is similar to that achieved by using a floating ball assembly, with the added advantage of placing the sensor below the surface of liquid. In applications where fouling is not expected or where there is insufficient space alternative mounting arrangements are available.



WaterTechw² C4E

Combined Conductivity, Salinity and Temperature Sensor

PRODUCT SPECIFICATION



Order Codes

Part No Description

- 223969 WaterTechw² C4E
Sensor (Cable Length:
20 metres)
- 223970 WaterTechw² C4E
Sensor (Cable Length:
20 metres)

Publication No: 132246DS-Iss12

The company reserves the right
to alter the specification without
prior notice. E&OE

BESTOBELL
AQUATRONIX
SINCE/DEPUIS 1953

Head Office

2880 Argentia Road, Unit 3
Mississauga, ON L5N 7X8
salesdesk@bestobell.com
1-800-668-3979
www.bestobell.com

Since 1953, Quality Products to Sense, Measure & Control
Depuis 1953, Produits De Qualités Pour Détecter, Mesurer & Contrôler

Physical

Dimensions

Weight

Protection Class

Enclosure Material

Cable Entries

Cable Type

Cable Length

177 mm x 27 mm (H x Diameter)

0.35 kg (Inc 10 metres of cable)

IP68

PVC Body, Stainless Steel

Integral Cable Gland

Polyurethane Coated

10 metres standard, 100 metres maximum

Environmental Data

Storage Temperature

Location

-10 to 60°C

Indoor/Outdoor

Electrical

Power Supply

12 Volts from Monitor

Interface to Monitor

Type

RS485

Measurement

Accuracy

Resolution

Conductivity

±1% FSD

0.01 to 1

(according to range)

Temperature

±0.5°C

0.01°C

Measurement Principle

Conductivity: 4 Electrode (2 Graphite, 2 Platinum)

Temperature: NTC

Range

µS/cm

mS/cm

Conductivity: 0-20.0µS/cm, 0-200.0µS/cm, 0-2000.0µS/cm

0-20mS/cm, 0-200mS/cm

Salinity: 5-60 ppt (g/Kg)

TDS - KCl 0-133,000 ppm

Temperature: 0-50°C

< 5 seconds

5 Bar

Response Time

Pressure Rating

Mounting

Installation Type

Mounting Shaft

Mounting Shaft/Bracket

Options - See Docs

Dip

0.5 to 3 metres in 0.5 metre increments

223980DS, 224567DS, 132584DS, 132571DS

Montréal Office

970 Montée de Liesse, #204

St-Laurent, QC H4T 1W7

ventes@bestobell.com

1-877-331-1225

Atlantic Office

166 North Side Road

Riverport, NS B0J 2W0

dmoosman@bestobell.com

902-529-0355

partech

Call us on 1.800.668.3979 www.partech.co.uk

Address: Rockhill Business Park, Higher Bugle, St Austell, Cornwall PL26 8RA, UK E: info@partech.co.uk